

CONQUEST THERMAL IMAGING SCOPE +LASER



MOBILE

CAPABLE



RESOLUTION: 384 X 288



PICTURE IN PICTURE

HOT TRACK



IPX67 WATERPROOF UP TO 30 MINS SUBMERGED TO 1 METER



1676 E. Semoran Blvd., Apopka, FL 32703

MODELS IR / IR-HD /LR / LR-HD

The Conquest-IR family is a shutterless infrared thermal imaging device that provides continuous and seamless image output as well as housing various lens options allowing for long-distance observation regardless of the scenario.

The Conquest-IR Heavy Duty takes almost everything that the Conquest-IR has and improves upon it. Using lenses with extended focal lengths, the Conquest-IR HD can more than double the observational abilities of its counterpart.

The Conquest-LR adds precise distance measurement functionality, allowing for further reliability of positioning and target searching to the Conquest-IR series.

The Conquest-LR Heavy Duty has the same precise distance measurement functionality as the Conquest-LR but uses lenses with extended focal lengths to provide greater observational abilities.

Lightweight and Compact: Weighing under 2 pounds, this thermal riflescope with laser range finder is designed for hunters who need a lightweight and comfortable viewing experience.

Impressive Detection Range: Equipped with a fast aperture F50/1.0 germanium lens, it offers a remarkable detection range of up to 7750 yards, allowing you to spot targets at long distances.

High-Contrast HD Display: The riflescope features a high-contrast HD AMOLED display with full-feature capabilities, including video recording, Wi-Fi, and compatibility with the Stream Vision 2 app for seamless integration with your smart devices.

Durable and Waterproof: Built tough with a IPX7 waterproof rating and shockproof construction, it can withstand adverse conditions.

Integrated Laser Rangefinder: Equipped with a laser range finder capable of measuring up to 1300 yds, allowing you to have confidence in your shot.



CONTACT US

sales@victoryoutdoorsusa.com

407.502.0145





CONQUEST	IR	IR-HD	LR	LR-HD
Detector	Uncooled VOx Microbolometer			
Resolution/Pixel Pitch	384×288/12µm	640×512/12µm	384×288/12µm	640×512/12µm
Objective Lens(F1.0)	19/25/35/50mm	25/35/55/75mm	19/25/35/50mm	25/35/55/75mm
Frame Rate, Hz	50Hz			
Display	0.39" OLED 1024×768			
Digital Zoom	1x, 2x, 4x			
Eyepiece Diopter	-5~+5			
Eye Relief	45mm			
Power Supply	Two 18650 Li-ion Batteries			
Standby Time	≥ 8h			
Weight (Without Battery)	≤ 570g (19/25/35mm); ≤ 620g (50mm)		≤ 670g (19/25/35mm); ≤ 720g (50mm); ≤ 735g (55mm); ≤ 820g (75mm)	
Dimensions	221×83×66mm (Including Eyepiece/Lens Covers)		221×83×100mm (Including Eyepiece/ Lens Covers)	
Interface	External Power / Type-C			
Operating Temperature	-30°C ~ +55°C			
Protection Rating	IP67			
Reliability	≥ 1200g Shock Resistance (19/25/35mm)		≥ 2000g Shock Resistance (50/55/75mm)	
Altitude	≥ 5000m			
Detection Range (Human)	19mm/1800m / 25mm/2370m / 35mm/3310m / 50mm/4730m			
Detection Range(Hog)	19mm/2430m / 25mm/3200m / 35mm/4480m / 50mm/6390m			



🔀 sales@victoryoutdoorsusa.com

wictoryoutdoorsusa.com

OUTDOORS

407.502.0145

CONTACT

US

1676 E. Semoran Blvd., Apopka, FL 32703